


FASERFIX®SUPER 500

FASERFIX®SUPER 500 with galvanised angle housings, up to load class F 900, Type 01, 1,0 m



F 900



■ Technical data:

Length mm	Width mm	Height mm	Weight kg	Inlaying depth	Internal channel cross-sect. cm ²	Item-no.
1000	590	630	302,55	40	2141	24121

■ Product description:

FASERFIX SUPER 500 type 01 - channel body made of fibre reinforced concrete, loading capacity from A 15 up to F 900 according to EN 1433, CE compliant, with galvanised steel angle housing and boltless quick-locking system SIDE-LOCK, eightfold locking, without crossing bars in the channel line, with safety joint, grating insertion depth 40 mm, L/W/H 1000x590x630 mm, item no. 24121

■ Material:

- **Channel body:** FASERFIX fibre-reinforced concrete
- **Angle housing:**


■ Type acc. DIN EN 1433:

M

■ Set of rules:

■ Application areas:

- Motorway service stations
- Military facilities
- Bus stations, bus stops
- Carriageways and roads (along)
- Fire brigade buildings
- Airfields, airports
- Port facilities, container stations
- Industrial buildings
- Industrial yards
- Cable ducts



- Sewage plants
- Truck parking areas
- Exhibition grounds, trade fairs
- Waste disposal sites
- Car parking facilities
- Ramps, Access to underground car parks
- Truck-Wash facilities
- Scrap metal yards
- Haulage companies, loading areas
- Road verge drainage
- Filling stations
- Underground car parks, multi-storey car parks
- Tunnel drainage
- Loading and cargo handling yards
- Access drives private

The optimal use of the product in the aforementioned applications depends on various factors (positioning, traffic load and frequency,...). Our experts will be happy to advise you!